

Jack capacity	Stroke	Model Number	Cylinder Effective Area	Oil Capacity	Collapsed Height	Extended Height	Outside Dia.	Cylinder Bore Dia.	Plunger Dia.	Weight
(tons)	(mm)		(in2)	(ln3)	A(in)	B(in)	D(in)	E(in)	F(in)	Kg(aprox)
5	25	RSC-51	0.99	0.99	4.34	5.34	1.50	1.13	1.00	1.0
	76	RSC-53	0.99	2.98	6.50	9.50	1.50	1.13	1.00	1.5
	127	RSC-55	0.99	4.97	8.50	13.50	1.50	1.13	1.00	1.9
	177	RSC-57	0.99	6.96	10.75	17.75	1.50	1.13	1.00	2.4
	232	RSC-59	0.99	9.07	12.75	21.88	1.50	1.13	1.00	2.8
10	26	RSC-101	2.24	2.24	3.53	4.53	2.25	1.69	1.50	1.8
	54	RSC-102	2.24	4.75	4.78	6.91	2.25	1.69	1.50	2.3
	105	RSC-104	2.24	9.23	6.75	10.88	5.25	1.69	1.50	3.3
	156	RSC-106	2.24	13.70	9.75	15.88	2.25	1.69	1.50	4.4
	203	RSC-108	2.24	17.89	11.75	19.75	2.25	1.69	1.50	5.4
	257	RSC-1010	2.24	22.65	13.75	23.88	2.25	1.69	1.50	6.4
15	25	RSC-151	3.14	3.14	4.88	5.88	2.75	2.00	1.63	3.3
	51	RSC-152	3.14	6.28	5.88	7.88	2.75	2.00	1.63	4.1
	101	RSC-154	3.14	12.57	7.88	11.88	2.75	2.00	1.63	5.0
	152	RSC-156	3.14	18.85	10.69	16.69	2.75	2.00	1.63	6.8
	203	RSC-158	3.14	25.13	12.69	20.69	2.75	2.00	1.63	8.2
25	26	RSC-251	5.16	5.16	5.50	6.50	3.38	2.56	2.25	5.9
	50	RSC-252	5.16	10.31	6.50	8.50	3.38	2.56	2.25	6.4
	102	RSC-254	5.16	20.63	8.50	12.50	3.38	2.56	2.25	8.2
	158	RSC-256	5.16	32.23	10.75	17.00	3.38	2.56	2.25	10.0
50	101	RSC-504	11.04	44.18	8.94	12.94	5.00	3.75	3.13	19.1
	159	RSC-506	11.04	69.03	11.13	17.38	5.00	3.75	3.13	23.1
	337	RSC-5013	11.04	146.34	18.13	31.38	5.00	3.75	3.13	37.6
75	156	RSC-756	15.90	97.41	11.25	17.38	5.75	4.50	3.75	29.5
100	102	RSC-1004	20.63	82.60	12.05	16.05	7.00	5.13	4.13	30.0
	168	RSC-1006	20.63	136.67	14.06	20.69	7.00	5.13	4.13	59.0