

Jackn capacity	Stroke	Model Number	Cylinder Effective Area	Oil Capacity	Collapsed Height	Extended Height	Outside Dia.	Cylinder Bore Dia.	Plunger Dia.	Weight
(tons)	(mm)		(in <sup>2</sup> )	(in <sup>3</sup> )	A(in)	B(in)	D(in)	E(in)	F(in)	Kg(aprox)
5	6	<b>RSSM-50</b>	0.99	0.25	1.28	1.53	2.31X1.63	1.13	1.00	1.0
10	12	<b>RSSM-100</b>	2.24	0.98	1.69	2.13	3.25X2.19	1.69	1.50	1.4
20	11	<b>RSSM-200</b>	4.43	1.94	2.03	2.47	4.00X3.00	2.38	2.00	3.2
30	13	<b>RSSM-300</b>	6.49	3.25	2.31	2.81	4.63X3.75	2.88	2.50	4.5
50	16	<b>RSSM-500</b>	9.62	6.01	2.63	3.25	5.50X4.50	3.50	2.75	6.8
75	16	<b>RSSM-750</b>	15.90	9.94	3.13	3.75	6.50X5.50	4.50	3.25	11.3
100	16	<b>RSSM-1000</b>	19.63	12.27	3.38	4.00	7.00X6.00	5.00	3.63	14.5
150	16	<b>RSSM-1500</b>	30.68	19.17	3.94	4.56	8.50X7.50	6.25	4.50	26.5