

Jack capacity	Stroke	Model Number	Cylinder Effective Area	Oil Capacity	Collapsed Height	Extended Height	Outside Dia.	Cylinder Bore Dia.	Plunger Dia.	Weight
(tons)	(mm)		(cm2)	(cm3)	(mm)	(mm)	(mm)	(mm)	(mm)	Kg (approx)
50	50	CSLS-502	70.9	355	128	128	125	95	95	14
	100	CSLS-504	70.9	709	178	178	125	95	95	18
	150	CSLS-506	70.9	1064	228	228	125	95	95	23
100	50	CSLS-1002	132.7	664	143	143	165	130	130	24
	100	CSLS-1004	132.7	1327	193	193	165	130	130	32
	150	CSLS-1006	132.7	1991	243	243	165	130	130	40
150	50	CSLS-1502	198.6	993	165	165	205	159	159	43
	100	CSLS-1504	198.6	1986	215	215	205	159	159	55
	150	CSLS-1506	198.6	2979	265	265	205	159	159	69
200	50	CSLS-2002	265.6	1330	193	193	235	183.9	183.9	66
	150	CSLS-2006	265.6	3989	443	443	235	183.9	183.9	101
300	50	CSLS-3002	456.2	2281	235	235	310	241	241	137
	150	CSLS-3006	456.2	6843	485	485	310	241	241	198
500	50	CSLS-5002	731.1	3656	295	295	400	305.1	305.1	289
	150	CSLS-5006	731.1	10967	545	545	400	305.1	305.1	390