

Jack capacity	Stroke	Model Number	Cylinder Effective Area	Oil Capacity	Collapsed Height	Extended Height	Outside Dia.	Cylinder Bore Dia.	Plunger Dia.	Weight
(tons)	(mm)		(in2)	(in3)	(in)	(in)	(in)	(in)	(in)	Kg (approx)
50	50	CSLS-502	10.99	21.63	6.46	8.43	4.92	3.74	Tr95x4	16.0
	100	CSLS-504	10.99	43.25	8.43	12.36	4.92	3.74	Tr95x4	21.0
	150	CSLS-506	10.99	64.88	10.39	16.30	4.92	3.74	Tr95x4	26.0
100	50	CSLS-1002	20.57	40.5	7.36	9.33	6.50	5.12	Tr130x6	31.0
	100	CSLS-1004	20.57	81	9.33	13.27	6.50	5.12	Tr130x6	39.5
	150	CSLS-1006	20.57	121.5	11.30	17.20	6.50	5.12	Tr130x6	48.0
150	50	CSLS-1502	30.78	60.58	8.23	10.20	8.07	6.26	Tr159x6	53.0
	100	CSLS-1504	30.78	121.17	10.20	14.13	8.07	6.26	Tr159x6	66.0
	150	CSLS-1506	30.78	181.75	12.17	18.07	8.07	6.26	Tr159x6	79.0
200	50	CSLS-2002	41.17	81.04	9.57	11.54	9.25	7.24	Tr184x6	83.0
	150	CSLS-2006	41.17	243.13	19.41	19.41	9.20	7.24	Tr184x6	118.0
300	50	CSLS-3002	70.71	139.19	11.61	13.58	12.20	9.49	Tr241x6	173.0
	150	CSLS-3006	70.71	417.56	21.46	33.27	12.20	9.49	Tr241x6	233.0
500	50	CSLS-5002	113.25	222.99	14.76	16.73	15.75	12.01	Tr305x6	367.0
	150	CSLS-5006	113.25	668.77	24.61	36.42	15.75	12.01	Tr305x6	617.0