

Jack capacity	Stroke	Model Number	Cylinder Effective Area	Oil Cap.	Coll. Height	Ext. Height	Out. Dia.	Cyl. Bore Dia.	Plungr Dia.	Saddle Dia.	Plunger Internal Thread	Plunger Thread Length	Collar Thread	Collar Thread Length	Center Hole Dia.	Weight Kg
(tons)	(mm)		(in2)	(in3)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(approx)
12	8	RSCH-120	2.76	0.86	2.19	2.50	2.75	2.13	1.38	-	3/4"-16UN	0.63	2 ^{3/4} "-16	1.19	0.77	1.5
	42	RSCH-121	2.76	4.49	4.75	6.38	2.75	2.13	1.38	-	-	-	2 ^{3/4} "-16	1.19	0.77	2.8
	42	RSCH-1211	2.76	4.49	4.75	6.38	2.75	2.13	1.38	-	3/4"-16UN	0.63	2 ^{3/4} "-16	1.19	0.77	2.8
	76	RSCH-123	2.76	8.29	7.25	10.25	2.75	2.13	1.38	-	-	-	2 ^{3/4} "-16	1.19	0.75	4.4
20	49	RSCH-202	4.73	9.46	6.38	8.38	3.88	2.88	2.13	2.13	1 ^{9/16} "-16UN	0.75	3 ^{7/8} "-12	1.50	1.06	7.7
	100	RSCH-204	4.73	18.99	9.54	13.55	3.88	2.88	2.13	2.13	1 ^{9/16} "-16UN	0.75	3 ^{7/8} "-12	1.50	1.06	11.0
	155	RSCH-206	4.73	28.67	12.05	18.11	3.88	2.88	2.13	2.13	1 ^{9/16} "-16UN	0.75	3 ^{7/8} "-12	1.50	1.06	14.1
30	64	RSCH-302	7.22	18.05	7.03	9.53	4.50	3.50	2.50	2.50	1 ^{13/16} "-16UN	0.88	4 ^{1/2} "-12	1.66	1.31	10.9
	156	RSCH-306	7.22	44.23	13.00	19.13	4.50	3.50	2.50	2.50	1 ^{13/16} "-16UN	0.88	4 ^{1/2} "-12	1.66	1.31	21.9
60	51	RSCH-602	12.73	31.83	7.81	9.85	6.25	4.88	3.63	3.61	2 ^{3/4} "-16UN	0.75	6 ^{1/4} "-12	1.91	2.12	20.5
	76	RSCH-603	12.73	38.20	10.00	12.75	6.25	4.88	3.63	3.61	2 ^{3/4} "-16U	0.75	6 ^{1/4} "-12	1.91	2.12	28.1
100	76	RSCH-1003	20.63	61.88	21.46	13.00	8.38	6.50	5.00	4.97	4"-16UN	1.00	8 ^{3/8} "-12	2.38	3.11	63.0