

Jack capacity	Stroke	Model Number	Max Cylinder Capacity		Cylinder Effective Area		Oil Capacity .		Coll. Height	Ext. Height	Out. Dia.	Cyl. Bore Dia.	Plungr Dia.	Plunger Internal Thread	Plunger Thread Length	Collar Thread	Collar Thread Length	Center Hole Dia.	Weight Kg
			Push	Pull	Push	Pull	Push	Pull											
(tons)	(mm)		(tons)		(in2)		(in3)		(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(approx)
30	178	RSCH-307	36.00	24.00	7.22	4.71	50.55	32.99	13.00	20.00	4.50	3.50	2.50	1 13/16"-16	0.88	4 1/2"-12	1.66	1.31	22.0
60	89	RSCH-603	64.00	42.00	12.73	8.37	44.57	29.21	9.75	13.25	6.25	4.88	3.63	2 3/4"-16	0.75	6 1/4"-12	1.91	2.13	28.0
	166	RSCH-606	64.00	42.00	12.73	8.37	82.77	54.24	12.75	19.25	6.25	4.88	3.63	2 3/4"-16	0.75	6 1/4"-12	1.91	2.13	35.5
100	76	RSCH-1003	103.00	68.00	20.63	13.54	61.88	40.64	10.00	13.00	8.38	6.50	5.00	4"-16	1.00	8 3/8"-12	2.38	3.13	61.0
	150	RSCH-1006	103.00	68.00	20.63	13.54	123.76	81.29	13.50	19.50	8.38	6.50	5.00	4"-16	1.00	8 3/8"-12	2.38	3.13	79.5
150	200	RSCH-1508	158.00	80.00	31.62	15.91	252.97	127.23	13.75	21.75	9.75	7.50	6.00	4 1/4"-16	1.00	-	-	3.13	111.0