

Jack capacity	Stroke	Model Number	Max Cylinder Capacity		Cylinder Effective Area		Oil Capacity		Coll. Capacity	Exttended Height	Outside Dia.	Cylinder Bore Dia.	Plunger Dia.	Weight Kg
			Push	Pull	Push	Pull	Push	Pull						
(tons)	(mm)		(tons)		(in2)		(in3)		A(in)	B(in)	D(in)	E(in)	F(in)	(approx)
10	254	RSR-1010	11.1	4.0	2.23	0.80	22.33	8.00	16.13	26.13	2.88	1.69	1.38	13.0
	305	RSR-1012	11.1	4.0	2.23	0.80	26.80	9.00	18.00	30.00	2.88	1.69	1.38	14.0
30	209	RSR-308	32.5	15.0	6.51	3.00	53.67	25.00	15.25	23.50	4.00	2.88	2.13	18.0
	368	RSR-3014	32.5	15.0	6.51	3.00	92.70	43.00	21.63	36.13	4.00	2.88	2.13	29.0
50	156	RSR-506	55.3	17.0	11.06	3.40	67.77	21.00	13.06	19.19	5.00	3.75	3.13	30.5
	334	RSR-5013	55.3	17.0	11.06	3.40	145.17	44.00	20.06	33.19	5.00	3.75	3.13	52.0
75	156	RSR-756	79.6	24.0	15.92	4.90	97.58	29.00	13.69	19.81	5.75	4.50	3.75	42.0
100	168	RSR-1006	103.2	48.0	20.65	9.60	136.93	63.00	14.06	20.69	7.00	5.13	3.75	61.5
150	57	RSR-1502	153.5	74.0	30.17	14.80	69.11	33.00	7.72	9.96	8.00	6.25	4.50	50.0
	156	RSR-1506	153.5	74.0	30.17	14.80	188.28	91.00	15.19	21.31	8.00	6.25	4.50	93.0
200	152	RSR-2006	221.0	112.5	44.21	22.50	265.28	135.00	16.94	22.94	99.75	7.50	5.25	147.5
300	153	RSR-3006	354.6	190.0	70.93	38.00	425.56	228.00	19.13	25.13	12.75	9.50	6.50	200.0
400	153	RSR-4006	475.4	255.0	95.09	51.00	570.51	306.00	21.19	27.19	14.13	11.00	7.50	304.0
500	153	RSR-5006	565.7	315.0	113.15	63.00	678.92	378.00	22.75	28.75	15.63	12.00	8.00	432.0